



COMPACT 350X

FLOOR SAW

The low weight and compact size combined with fast cutting speeds make the Compact 350X an ideal choice for all floor and road repair work in concrete and asphalt.



FEATURES & BENEFITS

- · Very low Hand Arm Vibration levels for the longest safe usage times.
- Easily transported (fi ts in the back of a small van).
- Specially moulded 25-litre detachable water tank.
- Foot operated depth adjustment for speed, simplicity and safety.
- Robust construction to survive the heaviest contract work.
- Adjustable handle height.
- Effective dust suppression.



VIBRATION DAMPING COMFORT **HANDLE**



REMOVABLE WATER TANK

TECHNICAL SPECIFICATIONS

Model	Compact 350X	
Part No.	CSXA01	
Engine Power	(Hp/kW)	11.8 / 8.7
Engine Model	(Honda)	GX390
Engine type	(Fuel)	Petrol
Blade Speed	(rpm)	3600
Max. Cutting Depth	(mm)	125
Blade Diameter	(mm)	350
Water Tank capacity	(ltr)	25
Width	(mm)	515
Height	(mm)	1019
Length	(mm)	771
Weight	(kg)	96
3-Axis Vibration	(m/sec ²)	2.8
Noise Level	(dB L _{WA})	114



POINTER GUIDE FOR **IMPROVED ACCURACY**



FOOT OPERATED DEPTH CONTROL





Sheen, Nr. Buxton, Derbyshire, SK17 OEU, GB Tel. +44 (0)1298 84606 - Fax +44 (0)1298 84722 Email: sales@altrad-belle.com

www.Altrad-Belle.com www.Altrad-Belle247.com

